



# OFFSET DISC HARROW

**Rigid Models 12-20 Ft.  
Folding Models 21-24 Ft.**

**5800 Series Offset Disc Harrow**



**Model 5817W Shown  
with 28" Blades**



**Model 5824W Shown -  
Transport Width 14'2"**

**Model 5824W Shown -  
Cutting Width 23'6"**

**The rugged 5800 Series performs primary tillage  
and boosts productivity with its advanced features!**

# KRAUSE... ENGINEERED FOR THE WAY YOU FARM

If your farming operation calls for a heavy-duty offset disc harrow, there's no better choice than a Krause 5800 Series. Krause 5800 Series offsets are renowned for their rugged dependability and heavy-duty construction. An innovative new rocker shaft design utilizes hydraulic cylinders that act directly on each wheel arm, reducing frame stress and torsion. Massive main frame beams are 6" x 8" x 3/8" structural steel with gang beams of 4" x 10" material. The 5800 Series offsets put from 497 lbs. to 650 lbs. per foot of cut to work on your toughest tillage challenges, depending on the model and blade. Gang angles are "pin-stop" adjustable from 16 degrees to 24 degrees.

## 5800 Series Specifications

Model	No. of Disk Blades	Disc Spacing	Cutting Width	Roading Width	No. of Bearing Arms	24" Blades Approx. Wt.	26" Blades Approx. Wt.	28" Blades Approx. Wt.
<b>(STANDARD MODELS)</b>								
5812W	31	10"	12'3"	13'6"	8	7267#	7741#	8395#
5814W	35	10"	13'10"	15'1"	9	7707#	8242#	8978#
5815W	39	10"	15'5"	16'7"	10	8094#	8759#	9562#
5817W	43	10"	17'0"	18'2"	12	8695#	9305#	10080#
5819W	47	10"	18'7"	19'9"	13	9539#	10311#	11155#
5820W	51	10"	20'2"	21'3"	14	9953#	10793#	11793#
<b>(FOLDING MODELS)</b>								
5821W	53	10"	21'0"	11'10"	18	11240#	11963#	12721#
5824W	59	10"	23'6"	14'2"	18	11705#	12514#	13464#
<b>(ROCK-FLEX MODELS)</b>								
5812WR	31	10"	12'3"	13'6"	8	7983#	8186#	8708#
5814WR	35	10"	13'10"	15'1"	9	8398#	8628#	9195#
5815WR	39	10"	15'5"	16'7"	10	9011#	9267#	9760#
5817WR	43	10"	17'0"	18'2"	12	9427#	9710#	10316#
5819WR	47	10"	18'7"	19'9"	13	10567#	10866#	11636#
5820WR	51	10"	20'2"	21'3"	14	10991#	11297#	12162#



Rock-Flex bearing standards are available on 5800 Series offsets. Rock-Flex bearing standards absorb shock from rocks and extend blade and bearing life. Bearings are encased in rubber for added shock protection.

## Standard Equipment

Cast Iron Spools  
 Disc Blades:  
 Std. Models, 24", 6 ga.; 26", 1/4"; 28", 3/16"  
 Rock-Flex, 24", 1/4"; 26", 1/4"; 28", 3/16"  
 Depth Control: (2) 4" x 10" Hydraulic cyl., remote stop.  
 Wing Fold: (4) 3 1/2" x 18" Hydraulic cyl.  
 Hitch: ductile cast, 2 1/8" x 2 1/2" slot  
 Hydraulic Hoses  
 Outrigger Extensions  
 Quick Adjustable Swing Tongue  
 Regreasable Superseal Bearings  
 Rigid Scrapers  
 Safety Chain  
 Tapered Blades  
 Tie Rods: 1 1/2" square alloy  
 Tie Rod Wrench  
 Tires: (4) 11L x 15" 8-ply  
 Transport Light Kit



The 5800's massive tongue features a handy "wrenchless" adjustment with 13 different settings. This makes it simple and easy for the operator to set the 5800 for the correct draft. Tongue is self-leveling with screw type adjustment for fore and aft leveling.



Krause's exclusive ratchet jack lateral rear gang adjustment makes it easy to fine tune leveling adjustments. Just loosen the gang bolts and use the handy ratchet jack to move the rear gang in or out.

## Optional Equipment

Clevis Type Hitch for 1 3/8" pin  
 Tongue Type Hitch for 1 1/2" pin



New rocker shaft design features square steel rocker shaft that smoothly pivots through hardened steel sleeves. Hydraulic cylinders (4" x 10") act directly on the wheel arms, greatly reducing torsion and stress on the unit's main frame... resulting in a smooth, even lifting force and long frame life.



Single location remote depth control, conveniently located at the front of the disc, makes it easier than ever to fine tune depth adjustments. This system allows the 5800 to return to the same depth after each pass. A convenient transport lock valve is located next to the depth control adjustment.

**KRAUSE**  
 KRAUSE CORPORATION  
 305 South Monroe  
 P.O. Box 2707  
 Hutchinson, KS 67504-2707  
 Phone 800-957-2873 FAX 620-663-6943  
 Visit our website at [www.krauseco.com](http://www.krauseco.com)

Continued product improvement is a Krause goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment and prices without prior notice and without changes on previous models.



Printed in U.S.A.